

# ECONODRY

## VENDED LIGHT COMMERCIAL DRYER

PRODUCT SPECS	Single KDE/KDG	Stack KSE/KSG
Capacity <i>lbs</i>	18	18 per pocket
Cylinder Volume <i>cu ft</i>	7	7
Net Weight <i>lbs</i>		
Electric	150	265
Gas	155	275
Crated Weight <i>lbs</i>		
Electric	160	280
Gas	165	290
Machine Dimensions <i>inch</i> WxDxH	26.875 x 28 x 44.375	26.875 x 28 x 78.19
Shipping Dimensions <i>inch</i> WxDxH	29 x 32.75 x 45.5	29 x 32 x 80
Motor Power <i>hp</i>	1/3	1/3
Exhaust Diameter <i>inch</i>	4	4
Exhaust Air Flow <i>cfm</i>	220	220
Gas Connection <i>inch</i>	3/8 NPT	3/8 NPT
Gas Heating <i>BTU/h</i>	25,000	25,000
Available Voltages/Amp		
Electric	120/240/60/1, 30 Amp	120/240/60/1, 30 Amp
Electric	120/208/60/1, 30 Amp	120/208/60/1, 30 Amp
Gas	120/60/1, 15 Amp	120/60/1, 15 Amp

\* Specifications subject to change without notice or obligation. Contact Girbau North America at (800) 256-1073 for dimensions not shown or for clarification.

