

## ON-PREMISE E-SERIES SOFT-MOUNT WASHER-EXTRACTOR

|                                             |                            |
|---------------------------------------------|----------------------------|
| Capacity <i>lbs</i>                         | 70                         |
| Cylinder Diameter <i>inch</i>               | 32.5                       |
| Cylinder Depth <i>inch</i>                  | 20.9                       |
| Cylinder Volume <i>cu ft</i>                | 9.9                        |
| Net Weight <i>lbs</i>                       | 1401                       |
| Crated Weight <i>lbs</i>                    | 1484                       |
| Machine Width <i>inch</i>                   | 41.5                       |
| Machine Depth <i>inch</i>                   | 50.9                       |
| Machine Height <i>inch</i>                  | 59.1                       |
| Door Opening <i>inch</i>                    | 16.8                       |
| Floor to Door <i>inch</i>                   | 23.6                       |
| Shipping Dimensions <i>inch</i><br>WxDxH    | 42.3 x 52 x 65.2           |
| Washing Speeds <i>rpm</i>                   | 16/21/26/36/42             |
| Spin Speeds <i>rpm</i>                      | 83/335/530/698/937         |
| G-force                                     | 3.17/52/130/225/405        |
| Static Force Transmitted <i>lbs</i>         | 1790                       |
| Dynamic Force Transmitted <i>lbs</i>        | 403                        |
| Frequency of Dynamic Force <i>Hz</i>        | 15.5                       |
| Available Voltages / Wire Conductor / Amp   |                            |
| Hot Water (standard)                        | 208-240/60/1, 2W+G, 20     |
| Electric Auxiliary Heat (optional)          | 208-240/60/1, 2W+G, 20     |
| Hot Water (standard)                        | 208-240/60/3, 3W+G, 10     |
| Electric Auxiliary Heat (optional)          | 208/60/3, 3W+G, 60         |
| Electric Auxiliary Heat (optional)          | 240/60/3, 3W+G, 60         |
| Steam Auxiliary Heat (optional)             | 208-240/60/3, 3W+G, 10     |
| Drain Diameter <i>inch</i>                  | 3                          |
| Water Inlets <i>inch</i>                    | 2 @ 3/4                    |
| Recommended Water Pressure <i>PSI</i>       | 30-60                      |
| Water Flow <i>gal/min</i>                   | 16                         |
| Steam Connection <i>inch</i>                | 1/2                        |
| Steam Pressure (optional) <i>PSI</i>        | 29-87                      |
| Steam Flow (optional) <i>lbs/h</i>          | 176                        |
| Total Power <i>kW</i>                       | 3.0                        |
| Electric Heating Power (optional) <i>kW</i> | 20.7 @ 240V<br>15.8 @ 208C |

\* Specifications subject to change without notice or obligation. Contact Sports Laundry Systems at (800) 256-1073 for dimensions not shown or for clarification.

