

ON-PREMISE E-SERIES SOFT-MOUNT WASHER-EXTRACTOR

Electric Auxiliary Heat (optional) 208/60/3, 3W+G, 60 Electric Auxiliary Heat (optional) 240/60/3, 3W+G, 60		
Cylinder Depth inch Cylinder Volume cu ft 11.3 Net Weight Ibs 1499 Crated Weight Ibs Machine Width inch Machine Depth inch Door Opening inch Floor to Door inch Shipping Dimensions inch WXDXH Washing Speeds rpm Spin Speeds rpm Basiles Static Force Transmitted Ibs Dynamic Force Transmitted Ibs Prequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter inch Recommended Water Pressure PSI 11.3 11.3 11.3 12.3 14.99 15.8 41.5 41.5 41.5 42.3 x 52 x 65.2 42.3	Capacity <i>lbs</i>	80
Cylinder Volume cu ft Net Weight Ibs Crated Weight Ibs Machine Width inch Machine Depth inch Machine Height inch Door Opening inch Floor to Door inch Shipping Dimensions inch WXDXH Washing Speeds rpm Spin Speeds rpm Static Force Transmitted Ibs Dynamic Force Transmitted Ibs Frequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter inch Water Inlets inch Recommended Water Pressure PSI 1583 1499 1499 1583 1499 1583 1499 41.5 42.3 x 52 x 65.2 42.3 x	Cylinder Diameter <i>inch</i>	32.5
Net Weight Ibs Crated Weight Ibs I583 Machine Width Inch Machine Depth Inch Machine Depth Inch Door Opening Inch Floor to Door Inch Shipping Dimensions Inch WXDXH Washing Speeds Inch Spin Speeds Inch Grore Static Force Transmitted Ibs Dynamic Force Transmitted Ibs Frequency of Dynamic Force Inch WXDXH Water (standard) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter Inch WALLS Washing Speeds Inch WXDXH WALLS WASHING SQUAR WALLS WALS	Cylinder Depth inch	23.5
Crated Weight Ibs Machine Width inch Machine Depth inch Machine Height inch Door Opening inch Floor to Door inch Shipping Dimensions inch WXDXH Washing Speeds rpm 21/26/36/42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted Ibs Dynamic Force Transmitted Ibs Prequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter inch 3 Water Inlets inch Recommended Water Pressure PSI 30-60	Cylinder Volume cu ft	11.3
Machine Width inch Machine Depth inch Machine Height inch Door Opening inch Floor to Door inch Shipping Dimensions inch WXDXH Washing Speeds rpm 21/26/36/42 Spin Speeds rpm 83/335/530/698/931 G-force Static Force Transmitted lbs Dynamic Force Transmitted lbs Prequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter inch Water Inlets inch Recommended Water Pressure PSI 30-60	Net Weight Ibs	1499
Machine Depth inch Machine Height inch Door Opening inch Floor to Door inch Shipping Dimensions inch WxDxH Washing Speeds rpm 21/26/36/42 Spin Speeds rpm 83/335/530/698/931 G-force Static Force Transmitted lbs Dynamic Force Transmitted lbs Frequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter inch Water Inlets inch Recommended Water Pressure PSI 30-60	Crated Weight <i>lbs</i>	1583
Machine Height inch Door Opening inch Floor to Door inch Shipping Dimensions inch WxDxH Washing Speeds rpm 21/26/36/42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs Dynamic Force Transmitted lbs Frequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter inch Water Inlets inch Recommended Water Pressure PSI 3.16.8 42.3 x 52 x 65.2 42.3 x 52	Machine Width inch	41.5
Door Opening inch Floor to Door inch Shipping Dimensions inch WXDXH Washing Speeds rpm 21/26/36/42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs Dynamic Force Transmitted lbs 1850 Dynamic Force Transmitted lbs 412 Frequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter inch 3 Water Inlets inch 2 @ 3/4 Recommended Water Pressure PSI 30-60	Machine Depth inch	50.9
Floor to Door inch Shipping Dimensions inch WXDXH Washing Speeds rpm 21/26/36/42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs Dynamic Force Transmitted lbs Frequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter inch 3 Water Inlets inch 2 @ 3/4 Recommended Water Pressure PSI 30-60	Machine Height <i>inch</i>	59.1
Shipping Dimensions inch WxDxH Washing Speeds rpm 21/26/36/42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs Dynamic Force Transmitted lbs Frequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter inch 3 Water Inlets inch 2 @ 3/4 Recommended Water Pressure PSI 30-60	Door Opening inch	16.8
WXDXH 42.3 x 52 x 65.2 Washing Speeds rpm 21/26/36/42 Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs 1850 Dynamic Force Transmitted lbs 412 Frequency of Dynamic Force Hz 15.5 Available Voltages / Wire Conductor / Amp 208-240/60/3, 3W+G, 10 Hot Water (standard) 208/60/3, 3W+G, 60 Electric Auxiliary Heat (optional) 208/60/3, 3W+G, 60 Steam Auxiliary Heat (optional) 208-240/60/3, 3W+G, 10 Drain Diameter inch 3 Water Inlets inch 2 @ 3/4 Recommended Water Pressure PSI 30-60	Floor to Door inch	23.6
Spin Speeds rpm 83/335/530/698/931 G-force 3.17/52/130/225/400 Static Force Transmitted lbs Dynamic Force Transmitted lbs 1850 Dynamic Force Transmitted lbs 412 Frequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter inch 3 Water Inlets inch Recommended Water Pressure PSI 30-60		42.3 × 52 × 65.2
G-force Static Force Transmitted Ibs Dynamic Force Transmitted Ibs Prequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter Inch Water Inlets Inch Recommended Water Pressure PSI 3.17/52/130/225/400 412 55.5 412 208-240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 60 208-240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 10 30-60	Washing Speeds <i>rpm</i>	21/26/36/42
Static Force Transmitted <i>lbs</i> Dynamic Force Transmitted <i>lbs</i> Frequency of Dynamic Force <i>Hz</i> Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter <i>inch</i> Water Inlets <i>inch</i> Recommended Water Pressure <i>PSI</i> 1850 208-240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 10 3 Water Inlets <i>inch</i> 2 @ 3/4	Spin Speeds rpm	83/335/530/698/931
Dynamic Force Transmitted <i>lbs</i> Frequency of Dynamic Force <i>Hz</i> Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter <i>inch</i> Water Inlets <i>inch</i> Recommended Water Pressure <i>PSI</i> 15.5 208-240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 60 208-240/60/3, 3W+G, 10 208-240/60/3, 3W+G,	G-force	3.17/52/130/225/400
Frequency of Dynamic Force Hz Available Voltages / Wire Conductor / Amp Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter inch Water Inlets inch Recommended Water Pressure PSI 15.5 208-240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 60 208-240/60/3, 3W+G, 10	Static Force Transmitted <i>lbs</i>	1850
Available Voltages / Wire Conductor / Amp Hot Water (standard) 208-240/60/3, 3W+G, 10 Electric Auxiliary Heat (optional) 208/60/3, 3W+G, 60 Electric Auxiliary Heat (optional) 240/60/3, 3W+G, 60 Steam Auxiliary Heat (optional) 208-240/60/3, 3W+G, 10 Drain Diameter <i>inch</i> 3 Water Inlets <i>inch</i> 2 @ 3/4 Recommended Water Pressure <i>PSI</i> 30-60	Dynamic Force Transmitted <i>lbs</i>	412
Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Drain Diameter <i>inch</i> Water Inlets <i>inch</i> Recommended Water Pressure <i>PSI</i> 208-240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 60 240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 60 240/60/3, 3W+G, 60 240/60/3, 3W+G, 60 240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 10 208-240/60/3, 3W+G, 60 208-240/60/60/60/60/60/60/60/60/60/60/60/60/60	Frequency of Dynamic Force Hz	15.5
Water Inlets <i>inch</i> 2 @ 3/4 Recommended Water Pressure <i>PSI</i> 30-60	Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional)	208-240/60/3, 3W+G, 10 208/60/3, 3W+G, 60
Recommended Water Pressure <i>PSI</i> 30-60	Drain Diameter inch	3
	Water Inlets inch	2 @ 3/4
Water Flow gal/min 16	Recommended Water Pressure PSI	30-60
	Water Flow gal/min	16
Steam Connection <i>inch</i> 1/2	Steam Connection inch	1/2
Steam Pressure (optional) PSI 29-87	Steam Pressure (optional) PSI	29-87
Steam Flow (optional) lbs/h 176	Steam Flow (optional) lbs/h	176
Total Power <i>kW</i> 4.2	Total Power kW	4.2
Electric Heating Power (optional) kW 20.7 @ 240V 15.8 @ 208V	Electric Heating Power (optional) kW	

^{*} Specifications subject to change without notice or obligation. Contact Sports Laundry Systems at (800) 256-1073 for dimensions not shown or for clarification.







