




VENDED EXPRESSWASH SOFT-MOUNT WASHER-EXTRACTOR

ExpressWash

Capacity Ibs	130
Cylinder Diameter inch	42.5
Cylinder Depth inch	24.4
Cylinder Volume cu ft	20.1
Net Weight <i>lbs</i>	4260
Crated Weight Ibs	4636
Machine Dimensions <i>inch</i> WxDxH	61.8 x 58.8 x 75.8
Door Opening inch	22
Floor to Door inch	32
Shipping Dimensions <i>inch</i> WxDxH	66.5 x 64.8 x 85
Washing Speeds rpm	13/18/24/30/36
Spin Speeds rpm	72/300/450/625/800
G-force	3.13/54/122/236/387
Static Force Transmitted <i>lbs</i>	4888
Dynamic Force Transmitted <i>lbs</i>	692
Frequency of Dynamic Force Hz	13.3
Available Voltages / Wire Conductor / A Hot Water (standard) Hot Water (standard) Electric Auxiliary Heat (optional) Electric Auxiliary Heat (optional) Steam Auxiliary Heat (optional) Steam Auxiliary Heat (optional)	208-240/60/3, 3W+G, 25 440-480/60/3, 3W+G, 20 208/60/3, 3W+G, 100 240/60/3, 3W+G, 125 208-240/60/3, 3W+G, 25 440-480/60/3, 3W+G, 20
Drain Diameter inch	3
Water Inlets inch	2 @ 1
Recommended Water Pressure PSI	30-60
Water Flow gal/min	26
Steam Connection inch	3/4
Steam Pressure (optional) <i>PSI</i>	29-87
Steam Flow (optional) <i>lbs/h</i>	397
Total Power kW	7.3
Electrical Heating Power (optional) <i>kW</i> 208/60/3 240/60/3	27.6 35.8







Specifications subject to change without notice or obligation. Contact Continental Laundry Solutions at (800) 256-1073 for dimensions not shown or for clarification.



