

# EH255 Tilt

## ON-PREMISE E-SERIES SOFT-MOUNT WASHER-EXTRACTOR

ARCHITECTURAL/MECHANICAL  
PRODUCT SPECIFICATIONS

|                                                        |                        |
|--------------------------------------------------------|------------------------|
| Capacity <i>lbs</i>                                    | 255                    |
| Cylinder Diameter <i>inch</i>                          | 51.6                   |
| Cylinder Depth <i>inch</i>                             | 32.1                   |
| Cylinder Volume <i>cu ft</i>                           | 38.8                   |
| Net Weight <i>lbs</i>                                  | 9343                   |
| Crated Weight <i>lbs</i>                               | 10098                  |
| Crated Weight-Tilt Assembly <i>lbs</i>                 | 1112                   |
| Machine Dimensions <i>inch</i><br>WxDxH                | 72.4 x 81 x 88.8       |
| Door Opening <i>inch</i>                               | 26.9                   |
| Floor to Door <i>inch</i>                              | 39.2                   |
| Shipping Dimensions <i>inch</i><br>WxDxH               | 76.8 x 83.5 x 88.4     |
| Shipping Dimensions-Tilt Assembly<br>WxDxH <i>inch</i> | 42.5 x 78 x 27.6       |
| Washing Speed <i>rpm</i>                               | 13/17/22/27/32         |
| Spin Speeds <i>rpm</i>                                 | 66/250/405/565/725     |
| G-force                                                | 3.2/46/120/234/385     |
| Static Force Transmitted <i>lbs</i>                    | 10555                  |
| Dynamic Force Transmitted <i>lbs</i>                   | 1482                   |
| Frequency of Dynamic Force <i>Hz</i>                   | 12.1                   |
| Available Voltages/Wire Conductor/Amp                  |                        |
| Hot Water (standard)                                   | 208-240/60/3, 3W+G, 40 |
| Hot Water (standard)                                   | 440-480/60/3, 3W+G, 20 |
| Steam Auxiliary Heat (optional)                        | 208-240/60/3, 3W+G, 40 |
| Steam Auxiliary Heat (optional)                        | 440-480/60/3, 3W+G, 20 |
| Drain Diameter <i>inch</i>                             | 5                      |
| Water Inlets <i>inch</i>                               | 2 @ 2                  |
| Recommended Water Pressure <i>PSI</i>                  | 30-60                  |
| Water Flow <i>gal/min</i>                              | 58                     |
| Steam Connection <i>inch</i>                           | 1                      |
| Steam Pressure (optional) <i>PSI</i>                   | 29-87                  |
| Steam Flow (optional) <i>lbs/h</i>                     | 794                    |
| Total Power <i>kW</i>                                  | 11                     |
| Compressed Air Connection <i>inch</i>                  | 3/8                    |
| Compressed Air Pressure <i>PSI</i>                     | 87-100                 |
| Compressed Air Flow <i>cfm</i>                         | 10                     |

\* Specifications subject to change without notice or obligation. Contact Sports Laundry Systems at (800) 256-1073 for dimensions not shown or for clarification.

