

# EH060

ARCHITECTURAL/MECHANICAL  
PRODUCT SPECIFICATIONS

## ON-PREMISE E-SERIES SOFT-MOUNT WASHER-EXTRACTOR

|                                                            |                         |
|------------------------------------------------------------|-------------------------|
| Capacity <i>lbs</i>                                        | 60                      |
| Cylinder Diameter <i>inch</i>                              | 30.5                    |
| Cylinder Depth <i>inch</i>                                 | 20.5                    |
| Cylinder Volume <i>cu ft</i>                               | 8.4                     |
| Net Weight <i>lbs</i>                                      | 1289                    |
| Crated Weight <i>lbs</i>                                   | 1338                    |
| Machine Dimensions <i>inch</i><br>WxDxH                    | 38.4 x 48.2 x 58.1      |
| Door Opening <i>inch</i>                                   | 16.8                    |
| Floor to Door <i>inch</i>                                  | 22.9                    |
| Shipping Dimensions <i>inch</i><br>WxDxH                   | 39.4 x 49.6 x 64.2      |
| Washing Speed <i>rpm</i><br>Logi Control<br>Inteli Control | 42<br>22/27/36/42       |
| Spin Speeds <i>rpm</i>                                     | 42/86/350/550/725/966   |
| G-force                                                    | 0.75/3.2/52/129/224/400 |
| Static Force Transmitted <i>lbs</i>                        | 1528                    |
| Dynamic Force Transmitted <i>lbs</i>                       | 291                     |
| Frequency of Dynamic Force <i>Hz</i>                       | 16.1                    |
| Available Voltages/Wire Conductor/Amp                      |                         |
| Hot Water (standard)                                       | 208-240/60/1, 2W+G, 15  |
| Hot Water (standard)                                       | 208-240/60/3, 3W+G, 15  |
| Electric Auxiliary Heat (optional)                         | 208/60/3, 3W+G, 50      |
| Electric Auxiliary Heat (optional)                         | 240/60/3, 3W+G, 60      |
| Steam Auxiliary Heat (optional)                            | 208-240/60/1 2W+G, 15   |
| Steam Auxiliary Heat (optional)                            | 208-240/60/3, 3W+G, 15  |
| Drain Diameter <i>inch</i>                                 | 3                       |
| Water Inlets <i>inch</i>                                   | 2 @ 3/4                 |
| Recommended Water Pressure <i>PSI</i>                      | 30-60                   |
| Water Flow <i>gal/min</i>                                  | 16                      |
| Steam Connection <i>inch</i>                               | 1/2                     |
| Steam Pressure (optional) <i>PSI</i>                       | 29-87                   |
| Steam Flow (optional) <i>lbs/h</i>                         | 176                     |
| Total Power <i>kW</i>                                      | 1.88                    |
| Electrical Heating Power (optional) <i>kW</i>              | 20.3                    |

\* Specifications subject to change without notice or obligation. Contact Poseidon Textile Care at (800) 256-1073 for dimensions not shown or for clarification.

