

HS6085 Stat

190LB CAPACITY INDUSTRIAL WASHER-EXTRACTOR

ARCHITECTURAL/MECHANICAL
PRODUCT SPECIFICATIONS

PRODUCT SPECS

Capacity <i>lbs</i>	190
Cylinder Diameter <i>inch</i>	51.6
Cylinder Depth <i>inch</i>	24.8
Cylinder Volume <i>cu ft</i>	30.1
Net Weight <i>lbs</i>	8281
Crated Weight <i>lbs</i>	8834
Machine Dimensions <i>inch</i> WxDxH	69.7 x 76.3 x 81.4
Door Opening <i>inch</i>	26.9
Floor to Door <i>inch</i>	31.8
Shipping Dimensions <i>inch</i> WxDxH	76.8 x 83.5 x 88.4
Washing Speeds <i>rpm</i>	21/26/36/32
Spin Speeds <i>rpm</i>	66/250/405/565/725
G-force	3.2/46/120/234/385
Static Force Transmitted <i>lbs</i>	9218
Dynamic Force Transmitted <i>lbs</i>	1157
Frequency of Dynamic Force <i>Hz</i>	12.1
Available Voltages / Wire Conductor / Amp	
Hot Water / Steam Auxiliary Heat	208-240/60/3, 3W+G, 30 Amp
Hot Water / Steam Auxiliary Heat	440-480/60/3, 3W+G, 15 Amp
Drain Diameter <i>inch</i>	5
Water Inlets <i>inch</i>	2 @ 2
Recommended Water Pressure <i>PSI</i>	30-60
Water Flow <i>gal/min</i>	58
Steam Connection <i>inch</i>	1
Steam Pressure (<i>optional</i>) <i>PSI</i>	29-60
Steam Flow (<i>optional</i>) <i>lbs/h</i>	794
Total Power <i>kW</i>	9
Compressed Air Connection <i>inch</i>	3/8
Compressed Air Pressure <i>PSI</i>	87-100
Compressed Air Flow <i>cfm</i>	10

* Specifications subject to change without notice or obligation. Contact Girbau Industrials at (800) 256-1073 for dimensions not shown or for clarification.

