

PRODUCT SPECS	PC12030	PC12033	PC12035
Number of Rolls	2		
Roll Diameter <i>inch</i>	48		
Cylinder Length <i>inch</i>	118	130	138
Ironing Speed <i>ft/min</i>	16 - 164		
Heating Surface <i>sq ft</i>	139.9	153.7	163.2
Maximum Heating Power <i>BTU/h</i>	1,381,917	1,518,403	1,603,707
Evaporation Capacity <i>cfm</i>	0.25	0.28	0.30
Steam Connection <i>inch</i>	2		
Steam Consumption <i>lbs/h</i>	1,620	1,790	1,874
Steam Pressure <i>PSI</i>	116 - 174		
Condensate Return <i>inch</i>	1 1/2		
Number of Exhaust Connections	1		
Ironer Exhaust Diameter <i>inch</i>	10		
Ironer Exhaust Flow <i>cfm</i>	1,942		
Ironer Exhaust Back Pressure (max) <i>inch wc</i>	4		
Electrical Power (all motors) <i>KVA</i>	25.3		
Available Voltages, Wire Conductor, Amp	Electric 208-240/60/3, 3W + G, 125 440-480/60/3, 3W + G, 63		
Compressed Air Connection <i>inch</i>	1/2		
Compressed Air Flow <i>cfm</i>	11		
Compressed Air Pressure <i>PSI</i>	87 - 94		
Net Weight Total <i>lb</i>	21,980	24,472	26,014
Net Weight First Roll <i>lb</i>	11,905	13,118	13,922
Net Weight Second Roll <i>lb</i>	10,075	11,354	12,092
Crated Weight Total <i>lb</i>	25,816	28,572	30,115
Crated Weight First Roll <i>lb</i>	13,823	15,168	15,972
Crated Weight Second Roll <i>lb</i>	11,993	13,404	14,143
Machine Width <i>inch</i>	174.1	186.6	193.7
Machine Depth <i>inch</i>	164.7 - 177*		
Machine Height <i>inch</i>	73.2 - 112.2**		
Crated Roll Width <i>inch</i>	181	201	201
Crated Roll Depth <i>inch</i>	88		
Crated Roll Height <i>inch</i>	90.6		

* Depends on small piece tray.

** Depends if handrail is used.

Specifications subject to change without notice or obligation. Contact Girbau Industrial at (800) 256-1073 for dimensions not shown or for clarification.

