

PRODUCT SPECS	PC8030	PC8033	PC8035
Number of Rolls	2		
Roll Diameter <i>inch</i>	32		
Cylinder Length <i>inch</i>	118	130	138
Ironing Speed <i>ft/min</i>	16 - 148		
Heating Surface <i>sq ft</i>	79.99	87.8	93.2
Maximum Heating Power <i>BTU/h</i>	853,035		
Evaporation Capacity <i>cfm</i>	0.16		
Gas Connection (natural gas) <i>inch</i>	3/4 NPT		
Gas Pressure (natural gas) <i>inch wc</i>	40.9 - 120		
Gas Flow (natural gas) <i>cfm</i>	15.6		
Gas Connection (LP gas) <i>inch</i>	3/4 NPT		
Gas Pressure (LP gas) <i>inch</i>	40.9 wc		
Gas Flow (LP gas) <i>lbs/h</i>	43		
Number of Exhaust Connections	2		
Ironer Exhaust Diameter <i>inch</i>	10		
Ironer Exhaust Flow <i>cfm</i>	1,271		
Ironer Exhaust Back Pressure (max) <i>inch wc</i>	4		
Burner Exhaust Diameter <i>inch</i>	8		
Burner Exhaust Flow <i>cfm</i>	385		
Burner Exhaust Back Pressure (max) <i>inch wc</i>	-0.02		
Electrical Power (all motors) <i>kVA</i>	18.65		
Available Voltages, Wire Conductor, Amp	208-240/60/3, 3W + G, 100 440-480/60/3, 3W + G, 50		
Compressed Air Connection <i>inch</i>	1/2		
Compressed Air Flow <i>cfm</i>	6.7		
Compressed Air Pressure <i>PSI</i>	87-94		
Net Weight (total) <i>lb</i>	14,518	15,587	16,303
Net Weight (first roll) <i>lb</i>	7,529	8,091	8,466
Net Weight (second roll) <i>lb</i>	6,989	7,496	7,837
Crated Weight (total) <i>lb</i>	18,742	20,005	20,721
Crated Weight (first roll) <i>lb</i>	9,641	10,300	10,675
Crated Weight (second roll) <i>lb</i>	9,101	9,705	1,046
Machine Width <i>inch</i>	174	185	194
Machine Depth <i>inch</i>	159 - 172*		
Machine Height <i>inch</i>	93 - 100*		
Crated Roll Width <i>inch</i>	181	201	201
Crated Roll Depth <i>inch</i>	88.2		
Crated Roll Height <i>inch</i>	87.8		

* Depends on small piece tray and/or handrail.

Specifications subject to change without notice or obligation. Contact Girbau Industrial at (800) 256-1073 for dimensions not shown or for clarification.

