

CG165-175+

PRODRY2+ DRYING TUMBLER

ARCHITECTURAL/MECHANICAL
PRODUCT SPECIFICATIONS

ProDry2+

Inverter Drive

Capacity lbs	up to 175
Cylinder Diameter inch	50.8
Cylinder Depth inch	42.5
Cylinder Volume cu ft	49.8
Net Weight lbs	
Gas	1400
Steam	1550
Crated Weight lbs (standard packaging)	
Gas	1480
Steam	1630
Machine Width inch	52.9
Machine Depth inch	69.8
Machine Height inch	94
Door Opening inch	27
Floor to Door inch	33.9
Shipping Dimensions inch WxDxH	52.1 x 73.8 x 99
Exhaust Diameter inch	12
Exhaust Air Flow cfm	2150
Exhaust Back Pressure (max) WCI	0.8
Required Makeup Air sq in	525
Gas Connection inch	1 NPT
Gas Heating BTU/h	395,000
Gas Pressure (max/recommended/min)	
Natural Gas wc	10.5 / 6.5 / 5
Propane wc	13 / 11 / 10
Steam Connection inch	3/4 NPT
Condensate Outlet Connection inch	1 NPT
Steam Heating BTU/h at 100 PSI	265,500

GAS/STEAM MODELS

AVAILABLE VOLTAGES	WIRE CONDUCTOR	FULL LOAD AMPS	RECOMMENDED BREAKER SIZE
200-240/50-60/3	3W+G	11	15
380-415/50-60/3	3W+G	7	15
440-480/50-60/3	3W+G	6	15

