


CA120

CONTINENTAL ON-PREMISE DRYING TUMBLER


ARCHITECTURAL/MECHANICAL PRODUCT SPECIFICATIONS

Capacity <i>lbs</i>	120
Cylinder Diameter <i>inch</i>	44.6
Cylinder Depth <i>inch</i>	42.1
Cylinder Volume <i>cu ft</i>	38.1
Net Weight <i>lbs</i>	1,440
Crated Weight <i>lbs</i>	1,500
Machine Width <i>inch</i>	49
Machine Depth <i>inch</i>	63.5
Machine Height <i>inch</i>	87.2
Door Opening <i>inch</i>	31.4
Floor to Door <i>inch</i>	25.9
Shipping Dimensions <i>inch</i> WxDxH	52 x 68 x 95
Exhaust Diameter <i>inch</i>	14
Exhaust Air Flow <i>cfm</i>	2,150
Exhaust Back Pressure (max) <i>WC/</i>	0.30
Required Makeup Air <i>sq in</i>	375
Electric Heating <i>kW</i>	72
Gas Connection <i>inch</i>	1 NPT
Gas Heating <i>BTU/h</i>	375,000
Gas Pressure (min/max) Natural Gas <i>wc</i> Propane <i>wc</i>	6 - 12 12 - 13
Steam Connection <i>inch</i>	1.25
Steam Heating <i>BTU/h</i>	365,000
Air Connection <i>inch</i> Pressure <i>PSI</i>	1/8 80
Reversing	Standard
Water <i>GHT</i> Pressure <i>PSI</i>	3/4 20-60

SIDE VIEW



BACK VIEW



GAS/LP/STEAM MODELS

AVAILABLE VOLTAGES	WIRE CONDUCTOR	FULL LOAD AMPS	RECOMMENDED BREAKER SIZE
208-240/60/3	3W+G	15	20
480/60/3	3W+G	8	15

ELECTRIC MODELS

AVAILABLE VOLTAGES	WIRE CONDUCTOR	FULL LOAD AMPS	RECOMMENDED BREAKER SIZE
208/60/3	3W+G	215	300
240/60/3	3W+G	188	250
480/60/3	3W+G	95	125

Specifications subject to change without notice or obligation.
Contact Continental Laundry Solutions at (800) 256-1073 for
dimensions not shown or for clarification.